

Major Stormwater Plan Form SW-002

OFFICIAL USE ONL	Υ.
Permit Number:	
Date Filed:	
Date Approved:	

Contact Informa	tion					
APPLICANT:		PROPERTY OW	NER:			
Name:	Big Box, LLC	Name:	Big Box, LLC			
Address:	1197 Duck Road	Address:	1197 Duck Road			
	Duck, NC 27949		Duck, NC 27949			
Telephone:	252-261-3934	Telephone:	252-261-3934			
E-Mail Address:	monica.thibodeau@carolinadesigns.com	E-Mail Address:	monica.thibodeau@carolinadesigns.com			
Property Inform	ation					
Physical Street A	Address: Caratoke Highway, Ha	rbinger, NC 2794	11			
Parcel Identifica	0125 000 0001 00	000				
FEMA Flood Zon	V					
TEMA FIOOD ZOI	le Designation:					
Request						
Project Descripti	ion: Commercial Building, Parking,	Drives, Utilities an	d Stormwater Infiltration Basin			
	bance activity: 65,423 sf		me of BMPs: 12,694 cf sf			
	verage: 36,513 sf	Proposed lot co	27 222			
TYPE OF REQUE		,				
900	ubdivision (10-year, 24-hour rate) ite plan (5-year, 24-hour rate)					
RationaNRCS N	TO CALCULATE PEAK DISCHARGE I Method Aethod (TR-55 and TR-20)					
□ Alternat	volume calculation for small sites (less t tive stormwater runoff storage analysis eam drainage capacity analysis					
	ize county officials to enter my prope nitted and required as part of this pro					
Applicant Property Owner	Albra This		1/27/25 Date			
Property Owner (s)						

*NOTE: Form must be signed by the owner(s) of record, contract purchaser(s), or other person(s) having a recognized property interest. If there are multiple property owners/applicants a signature is required for each.



Stormwater Management Report Narrative, Calculations and Supporting Documentation

Project:

BIG BOX, LLC

COMMERCIAL SITE DEVELOPMENT

Harbinger,

Currituck County,

North Carolina

Prepared By:

Bissell Professional Group

P.O. Box 1068 3512 N. Croatan Highway Kitty Hawk, North Carolina 27949

January 31, 2025



Table of Contents

Stormwat	ter Ma	nagement Narrative	1-5
	Table	of Contents	1
	Proje	ct Overview & Proposed Developmental Activities	2
	Exist	ing Site Conditions, Topography and Drainage Features	2
	Site S	oils	2
	Over	view of Stormwater Management Design Criteria	3
	Over	view of Stormwater Management Features by Drainage Area	3
		ation & Maintenance	
Attachme	ents		
	A:	Site Maps	
	B :	Drainage Area Delineation Maps	
	C:	Soils Report	
	D:	Stormwater Management Calculations (Sealed Under Cover)	
	E:	Sedimentation and Erosion Control Calculations (Sealed Under	r Co

STORMWATER MANAGEMENT NARRATIVE:

PROJECT OVERVIEW & PROPOSED DEVELOPMENTAL ACTIVITIES

The following project requires a coastal county stormwater management permit pursuant to North Carolina Administrative Code Section: 15A NCAC 2H.1000, Rules for Stormwater Management. Proposed development activities require an erosion and sediment control permit and with a built-upon area density greater than 24%, the project is considered High Density. The project is slated for development along the west side of Caratoke Highway, US HWY 158 in the Harbinger area of Currituck County. Proposed developmental activities include the following;

- a) 8,300 sf Commercial Building with Front Porch
- b) 2,322 sf Canopy over a Loading Area
- c) Concrete Driveways and Parking
- d) Gravel access connections to adjoining properties
- e) Stormwater Management and Utility Improvements

Please reference the **Development Overview Map** provided under **Attachment** A.

EXISTING SITE CONDITIONS, TOPOGRAPHY AND DRAINAGE FEATURES

The rear 10.3-acres of the property was formerly utilized for a sand mining operation with the excavation having since been reclaimed as a lake. The front 1.3-acre portion that provided access to the mine is now vacant woodlands and is the site for proposed development. Topography across the front is generally flat at an average ground surface elevation of 7.5 ft-msl. Remnant berms from the mine operation still exist around the perimeter with some reaching an elevation of 10.0 ft-msl. Surrounding development includes commercial, vacant woodlands and a golf course. The front portion of the property primarily drains east from a low ridge along the lake to the roadway ditch along the west side of Caratoke Hwy. From there it drains south and then east under the highway to a tributary known as Pan Ridge Ditch that ultimately discharges to the Currituck Sound, classified as SC waters.

Please reference the **USGS 7.5 Minute Quadrangle Site Location Map** under **Attachment A**. Please reference the **Existing Site Features Map** provided in the **Construction Drawings**

SITE SOILS

Pursuant to the USDA Soil Survey Manual of Currituck County, soils across the proposed development area are composed of Conetoe & Nimmo Loamy Sands. Conetoe soils are described as well drained with moderately rapid permeability. Nimmo soils are described as poorly drained with moderate to moderately rapid permeability.

Protocol Sampling Service, Inc. conducted on-site evaluations to determine the presence of restrictive horizons, seasonal high-water table conditions and permeability capabilities of the underlying soils. A total of four (4) borings were advanced across the site, (3) in the vicinity of the proposed infiltration basin and (1) near the proposed wastewater disposal system.

Findings of the evaluations concluded that compacted soils found in the vicinity of the infiltration basin will need to be removed to a depth of 30 inches below the surface and replaced with clean fine to medium sand to the expected bottom elevation of the infiltration basin. The undercut and backfill will help to level the 4.82 ft-msl seasonal high-water table elevation across the area and ensure an infiltration rate of 18 inches/hour within the basin.

For additional details, please reference the **Soils Report** provided under **Attachment C**.

OVERVIEW OF STORMWATER MANAGEMENT DESIGN CRITERIA

NORTH CAROLINA DEPARTMENT OF ENVIRONMENTAL QUALITY

Supplemental to North Carolina's General Statues, Session Laws and other Administrative Codes, 15A NCAC 02H.1019 sets forth rules governing stormwater management of developmental activities within the state's 20 Coastal Counties. These rules intend to protect surface waters of the state by controlling pollutants associated with stormwater runoff applicable to the development of land for residential, commercial, industrial, or institutional uses. The proposed developmental activities of this project shall comply with the following:

- I. The proposed development requires an Erosion and Sedimentation Control Plan approval, is Non-Residential in nature, proposes to add greater than 10,000 sf of built-upon area, and, therefore, shall obtain a Stormwater Management Permit.
- II. Stormwater runoff from the proposed development will ultimately drain to surface waters of the Currituck Sound. These waters are classified as "SC" and, in accordance with Rule .1019(5)(c), subject the development to the coastal stormwater program requirements set forth for "Other Coastal County Water."
- III. The proposed development will have an overall built upon area density greater than 24% percent and, therefore, in accordance with Rule .1019(6)(a), is considered "High-Density" and is required to manage a 1.5 inch rainfall event.
- IV. In accordance with Rule .1003(3)(a), High Density projects are required to utilize Stormwater Control Measures (SCM) to treat runoff from the design rainfall event. For this project, an infiltration basin will be employed that must meet the Minimum Design Criteria (MDC) outlined in Rule .1051, MDC for Infiltration Systems, and applicable chapters of the "Stormwater Design Manual."

CURRITUCK COUNTY

In addition to NCDEQ's high-density permitting requirements, the development's stormwater management system shall also be designed in accordance with the standards prescribed for Major Site Plans as outlined in Chapter 7.3 of the Currituck County UDO and Chapter 2.4 of the Currituck County Stormwater Manual. Among other provisions, the following primary standards shall be met:

- I. Major Site Plans shall implement adequate stormwater practices to reduce the post-development peak discharge from the 24-hour storm event with a 5-year recurrence interval down to the predevelopment discharge rate from the 24-hour storm event with a 2-year recurrence interval based on pre-development conditions from a wooded site, regardless of actual pre-development site conditions.
- II. Major Site Plans shall provide Minimum Building Pad Elevations required to prevent flooding from the 24-hour storm event with a 10-year recurrence interval.
- III. Finished Floor Elevations for all principal structures shall be above the 100-year Regulatory Flood Protection Elevation, or 18 inches above the 24-hour storm event with a 10-year recurrence interval, or at least 6 inches above a filled septic system, whichever is greater.

OVERVIEW OF STORMWATER MANAGEMENT FEATURES BY DRAINAGE AREA

Developmental activities will consist of those previously itemized in the "Project Overview and Proposed Development Activities" section above. Like Pre-Development drainage conditions, proposed grading and drainage improvements form a single primary Post-Development Drainage Area [#1] and two small residual Drainage Areas [#2 & #3].

Please reference Pre and Post Development Drainage Area Delineation Maps under Attachment B

Drainage Area #1

This is the project's primary drainage area that drains east to the roadway ditch along the west side of Caratoke Hwy. The on-site area totals approx. 1.20 acres in the Pre-Development condition and will increase slightly to approx. 1.27 acres in the proposed Post-Development state. Development will include nearly all of the proposed built-upon area and the following stormwater management improvements:

Collection

Stormwater runoff from the northern half of the proposed commercial building and the adjoining parking & drive aisle areas will sheet flow to a network of catch basins located within the parking area. Once collected, runoff will be conveyed by a series of pipes to the northeast corner of the proposed infiltration basin for treatment and disposal. Stormwater runoff from the southern half of the commercial building, the rear loading area and the front drainfield area will be collected by a typical vegetated swale running along the southern property boundary. The swale is sloped to convey runoff to the southeast corner of the infiltration basin. The proposed gravel access road located along the north side of the infiltration basin is superelevated to promote sheet flow across the vegetated shoulder and into the basin.

Stage and Storage

In accordance with the NCDEQ and County Design Criteria outline above, the Infiltration Basin has been designed with an open storage capacity capable of accommodating runoff in excess of both the 1.5 inch rainfall event and the Post-Development 5 year - 24 hour storm event.

The following is a summary of design conditions:

STAGE ELEVATIONS

•	Seasonal high-water table elevati	on = 4.82 ft-msl	(See Site Soils section above)
•	Basin Bottom Elevation	=6.90 ft-msl	(Provides required 2' of separation to SHWT)
•	1.5" rainfall event stage	= 7.40 ft-msl	(See NCDEQ Calculations)
•	5 yr – 24 hr event stage	= 8.00 ft-msl	(See Currituck Calculations*)
•	10 yr - 24 hr event stage	= 8.18 ft-msl	(See EPA SWMM Model Results)
•	Minimum Basin Top Elevation	= 8.50 ft-msl	(See grading and drainage plan)

STORAGE VOLUMES

•	1.5" rainfall event storage	= 3,128 cf	(See NCDEQ Calculations)
•	5 yr-24 hr event storage	= 8,392 cf	(See Currituck Calculations*)
•	10 yr-24 hr event storage	= 9,932 cf	(See EPA SWMM Model Results)
•	Basin storage capacity	= 12,694 cf	

^{*}Sections 2.4.3 and 2.4.4 of the Currituck County Stormwater Manual allows the use of "Rational Method" and "Simple Volume Calculations" determine runoff rates and required storage volumes for sites under 10 acres.

Treatment

Primary treatment will be provided by the proposed Infiltration Basin. Measures of Pre-treatment will also be provided by the leading vegetative swales and sumps provided within the proposed catch basins. Runoff from the rear loading area and gravel access road will also receive pre-treatment by sheet flowing over vegetated shoulders before entering into the infiltration basin. Longitudinal slopes of the proposed swales and pipe collection network are kept to a minimum to reduce flow velocities, reduce erosion and promote infiltration.

Disposal & Overflow

Infiltration is the primary source of disposal and drawdown calculations resolve that the <u>basin's full</u> <u>capacity volume</u> will infiltrate into the site's excessively drained sandy soils in a period of approximately 2.30 hours, or 0.10 days. This is significantly less than the maximum 72 hour allowance prescribed by NCDEQ. In the event that the system capacity is exceeded, excess runoff will begin to overflow the western bank of the infiltration basin (8.50 ft-msl) and sheet flow towards the on-site lake. During exceptional events, stormwater will also backflow out of the catch basins and the east end of the southern boundary swale and flow into the ditch along Caratoke Highway.

Building Pad Elevation (BPE) and First Floor Elevation (FFE)

- Finished building pad elevations located immediately around the perimeter of the building are set at, or above 9.5 ft-msl. This provides <u>1.3'</u> of separation to the 10 yr-24 hour storm event stage of 8.2 ft-msl.
- First floor elevation of proposed building is set at 10.5 ft-msl, providing 2.3' of separation to the 10 yr-24 hr storm event stage of 8.2 ft-msl. The site is located in a FEMA X Flood Zone so there is no base flood or regulatory flood protection elevation. Finished grade elevations across the drainfield average around 9.5 ft-msl, providing 12" of separation to the finished first floor elevation.

Drainage Areas #2 & #3

These are small residual drainage areas at the rear of the project that drain north and south to existing low-lying areas off-site. The on-site areas total approx. 0.11 acres in the Pre-Development condition and will be reduced to 0.04 acres in the Post-Development state. Improvements include the grading necessary to return to surrounding off-site elevations and a small (215 sf+/-) portion of the proposed gravel access road where it connects to the existing path around the lake. Runoff from these areas should be considered minimal and will continue to drain much like existing conditions.

Please reference **Stormwater Management Calculations** under **Attachment D**, **Erosion Control Calculations** under **Attachment E** and the **Construction Drawings** for more details.

OPERATION & MAINTENANCE


The NCDEQ stormwater permit holder is obligated to maintain the development's stormwater management system as outlined and executed in the Operation and Maintenance Agreements submitted with the State Stormwater Permit application and as denoted on the construction drawings prepared by Bissell Professional Group title "CONSTRUCTION DRAWINGS FOR BIG BOX, LLC COMMERCIAL SITE DEVELOPMENT." The following is a general overview of some, but possibly not all, maintenance responsibilities;


- **A.** For purposes of operating and maintaining the infiltration basin, access must be maintained such that entire perimeter of the basin can be reached by light construction equipment.
- **B.** All provisions of the "Infiltration Basin Operation and Maintenance Agreement" executed in part with the NCDENR permit application shall be performed.
- **c.** During construction, erosion shall be kept to a minimum and any eroded areas of the vegetated conveyances shall be repaired immediately. During the course of construction, the area of the proposed infiltration basin may be used as a temporary sediment basin. Please refer to the Infiltration Basin Construction Sequence Notes provided on the construction drawings for further details.

For purposes of access and maintenance, the permit holder shall establish Drainage Easements in accordance with those outlined in the Construction Drawings noted above.

ATTACHMENT A — SITE MAPS


- USGS 7.5 Minute Quadrangle Site Location Map
- Development Overview Map (Reduction)








ATTACHMENT B - DRAINAGE AREA DELINEATION MAPS

- NCDEQ Post Development Drainage Area Map used for Simple Method Calculations
- Currituck Pre Development Drainage Area Map used for Rational Method Calculations
- Currituck Post Development Drainage Area Map used or Rational Method Calculations
- Post Development Drainage Map used for EPA SWMM Model










ATTACHMENT C — SOILS REPORT

Soils Report - Protocol Sampling Service, Inc.



Protocol Sampling Service, Inc. "Experts in Environmental Compliance"

(919) 210-6547

Protocolsampling@yahoo.com Environmentalservicesnc.com

4114 Laurel Ridge Drive Raleigh, North Carolina 27612

December 31, 2024

Mr. David Klebitz, P.E. Bissell Professional Group, Inc. Post Office Box 1068 Kitty Hawk, North Carolina 27949

Re: Storm Water Management Soil Investigation

Big Box, LLC Caratoke Highway Harbinger, Currituck County, North Carolina Protocol Job No. 24-194

Dear Mr. Klebitz:

The following Soil Investigation is submitted to assist in a site assessment for the proposed storm water management improvements associated with the Big Box, LLC project south of 8760 Caratoke Highway in Harbinger, North Carolina. The study area is being considered for one (1) infiltration basin.

SITE HISTORY AND PHYSICAL CHARACTERISTICS

Commercial and residential development surround the study area. The site was used as a commercial sand pit for at least 20-years with an access road and staging area in the proposed storm water basin location. Protocol Sampling Service, Inc. of Raleigh, North Carolina was hired to perform an investigation to identify the depth to seasonal high-water table, if any restrictive layers are present and determine subsurface permeabilities at or slightly below the expected infiltration basin bottom.

SOIL INVESTIGATION

The field survey was conducted on Thursday, November 21 and Thursday, December 12, 2024. Four (4) soil borings were advanced from 48 to 60-inches below land surface (bls) with a hand auger in and around the proposed basin as shown on the attached exhibit. Soil color was determined with a Munsell Soil Color Chart. The presence of fill or other disturbances, the depth to the seasonal high-water table, soil structure and consistence were noted. The borings were also checked for reduced colors, an anaerobic smell or obvious soil wetness. Surface elevations range from 7.29 feet msl to 7.74 feet msl from west to east across the study area.

FINDINGS - Soil

 The subject property contains soil belonging to the Conetoe series. The Conetoe series is a loamy, mixed, thermic, Arenic Hapludult. The soil profile was found to be compacted in areas previously used as the sand pit access road and associated staging areas.

- The Conetoe series soil was found to have an apparent depth to seasonal high-water table of 22-inches bls in soil boring No.1 (elevation 5.51'-msl), 20-inches bls in soil boring No.2 (elevation 6.08'-msl), 30-inches bls in soil boring No.3 (elevation 4.82'-msl) and 30-inches bls in the soil boring No.4 (elevation 4.29'-msl). Static water levels were found at 3.41'-msl in soil boring No.3, to 3.79'-msl in Soil boring No.4.
- Cemented soil was encountered to a depth of 24 to 30-inches in soil borings 1, 2 and 3; all due to the proximity of the borings to the access road and staging areas used by dump trucks to load and carry sand from the sand pit offsite.

FINDINGS - Conductivity

• HYDRAULIC CONDUCTIVITY TESTING

- Initial saturated hydraulic conductivity testing, (Ksat 1 at Boring 1), was performed on November 21, 2024 to determine the subsurface permeability in the center of the proposed infiltration basin at the infiltrative elevation of 32-inches bls at an elevation of 4.67'-msl, 0.84' above the seasonal high-water elevation and at least one-foot above the static water table elevation. The saturated hydraulic conductivity test (Ksat) reached steady state readings within five minutes and three consecutive readings revealed an average conductivity of 0.564 inches/hour; well below what would be expected for an undisturbed sandy soil.
- Subsequent saturated hydraulic conductivity testing was performed on December 12, 2024 to determine the subsurface permeabilities outside of the proposed basin in native, undisturbed soil (Ksat 2 at Boring 4) and at the edge of the basin below the compacted soil (Ksat 3 at Boring 3). Ksat 2 reached steady state readings immediately and three consecutive readings revealed an average conductivity of 6.106 inches/hour. Ksat 3 run inside the proposed infiltration basin, reached steady state readings immediately and three consecutive readings revealed an average conductivity of 18.676 inches/hour; exactly what would be expected for an undisturbed sandy soil.

Conclusions

- Removal of all compacted soil to a depth of 30-inches below land surface and replace with clean fine to medium sand to the expected basin bottom of 6.90'-msl.
- This will ensure that the stormwater will infiltrate into the basin and into the surficial aquifer at a rate of 18-inches/hour.

The findings presented herein are based on the site conditions observed during performance of the field survey on Thursday, November 21 and Thursday, December 12, 2024.

Please call me at (919) 210-6547 if you have any questions or need further assistance.

Sincerely,

Protocol Sampling Service, Inc.

David E. Meyer, N.C.L.S.S.

President

Soil Profile Description

SB-3

- A/E 0-18 inches; dark brown (7.5YR 3/3) loamy fine sand; cemented; firm.
- Bt 18-30 inches; brownish yellow (10YR 6/8) sandy loam; cemented; friable.
- $C1 \hspace{1cm} 30-48 \hspace{0.1cm} inches; \hspace{0.1cm} brown \hspace{0.1cm} ish \hspace{0.1cm} yellow \hspace{0.1cm} (10YR \hspace{0.1cm} 6/8) \hspace{0.1cm} and \hspace{0.1cm} very \hspace{0.1cm} pale \hspace{0.1cm} brown \hspace{0.1cm} (10YR \hspace{0.1cm} 7/4) \hspace{0.1cm} sand \hspace{0.1cm} with \hspace{0.1cm} strong \hspace{0.1cm} brown \hspace{0.1cm} (7.5YR \hspace{0.1cm} 5/6) \hspace{0.1cm} and \hspace{0.1cm} very \hspace{0.1cm} pale \hspace{0.1cm} brown \hspace{0.1cm} (10YR \hspace{0.1cm} 7/4) \hspace{0.1cm} sand \hspace{0.1cm} with \hspace{0.1cm} strong \hspace{0.1cm} brown \hspace{0.1cm} (7.5YR \hspace{0.1cm} 5/6) \hspace{0.1cm} and \hspace{0.1cm} very \hspace{0.1cm} pale \hspace{0.1cm} brown \hspace{0.1cm} (10YR \hspace{0.1cm} 7/4) \hspace{0.1cm} sand \hspace{0.1cm} with \hspace{0.1cm} strong \hspace{0.1cm} brown \hspace{0.1cm} (7.5YR \hspace{0.1cm} 5/6) \hspace{0.1cm} and \hspace{0.1cm} very \hspace{0.1cm} pale \hspace{0.1cm} brown \hspace{0.1cm} (10YR \hspace{0.1cm} 7/4) \hspace{0.1cm} sand \hspace{0.1cm} with \hspace{0.1cm} strong \hspace{0.1cm} brown \hspace{0.1cm} (7.5YR \hspace{0.1cm} 5/6) \hspace{0.1cm} and \hspace{0.1cm} very \hspace{0.1cm} pale \hspace{0.1cm} brown \hspace{0.1cm} (10YR \hspace{0.1cm} 7/4) \hspace{0.1cm} sand \hspace{0.1cm} with \hspace{0.1cm} strong \hspace{0.1cm} brown \hspace{0.1cm} (7.5YR \hspace{0.1cm} 5/6) \hspace{0.1cm} and \hspace{0.1cm} very \hspace{0.1cm} and \hspace{$

concentrations and gray (10YR 6/1) depletions; single grained; loose.

Ksat 3 (32")

C2 48 – 60 inches; brownish yellow (10YR 6/8) fine sand; single grained; loose

Soil Series: Conetoe - disturbed/compacted

Landscape: Coastal Plain Landform: terrace

Parent Material: Marine sediments Drainage Class: moderately well drained

Particle Size Class: sandy Temperature Regime: thermic

Subgroup Classification: Arenic Hapludult

Examination Method: auger boring

Date: December 12, 2024 Weather: Clear, 55 Investigators: David Meyer

Shwt: 30"

Measured water table depth: 47"

SATURATED HYDRAULIC CONDUCTIVITY STUDY

Big Box LLC

2-ON

Date:	#########	11/2/24			Weather Condition:	sunny	
Location:	SB-1	Conetoe			Temperature (F):	60	
Number:	Ksat 1						
Horizon:	C					cm	in
Depth(inches):	32.0	h20 59"	SET	<u>r up</u>	Target Water Level:	15.2	6.0
			cm	in	eginning Water Level:	15.2	6.0
Н	lole Depth:		81.3	32.0	Ending Water Level:	15.2	6.0
	Reference:	+	10.2	4.0			
	Head:	-	15.2	6.0			
CHT Tube	(s) setting:	-	76.2	30.0	Hole diameter (d):	5.0	cm
					Hole radius (r):	2.5	cm
Val	ve Setting:		X		coefficient A:	0.001136	

NOTE: Readings based on Ending Water Level

Coversion Factor (C.F.): 105.0

1-ON

Water	Change in	Chamber	Clock	Elapse	d Time	Q	K	K	K
Reading	Water Leve	C.F.	Time (min)	(min)	(hr)	(cm3/hr)	(cm/hr)	(in/hr)	gal/ft2/day
46			0.0						
44			3.0						
43	1.0	105.0	4.0	1.00	0.017	6300.0	7.1582	2.8182	42.165
42.8	0.2	105.0	5.0	1.00	0.017	1260.0	1.4316	0.5636	8.433
41.5	1.3	105.0	10.0	5.00	0.083	1638.0	1.8611	0.7327	10.963
38.5	3.0	105.0	20.0	10.00	0.167	1890.0	2.1475	0.8455	12.649
36.5	2.0	105.0	30.0	10.00	0.167	1260.0	1.4316	0.5636	8.433
34.5	2.0	105.0	40.0	10.00	0.167	1260.0	1.4316	0.5636	8.433
32.5	2.0	105.0	50.0	10.00	0.167	1260.0	1.4316	0.5636	8.433
						Final Ksat	1.432	0.564	8.433

	SATURA	TED HYDRA			TY STUDY		
		, в	ig Box LLC				
Date:	########	hlizhy			Weather Condition:	sunny	
Location:	SB-4	Conetoe			Temperature (F):	45	
Number:	Ksat 2						
Horizon:	С					cm	in
Depth(inches):	30.0	H20 42"	SE1	T UP	Target Water Level:	15.2	6.0
			cm	in	eginning Water Level:	10.2	4.0
F	Hole Depth:		76.2	30.0	Ending Water Level:	10.2	4.0
	Reference:	+	0.0	0.0			
	Head:	- 1	0.0	0.0			
CHT Tube	(s) setting:	=	76.2	28.0	Hole diameter (d):	5.0	cm
					Hole radius (r):	2.5	cm
Val	lve Setting:		X		coefficient A:	0.002045	
		1 ON	2.01				

NOTE: Readings based on Ending Water Level

Coversion Factor (C.F.): 105.0

Water	Change in	Chamber	Clock	Elapse	d Time	Q	K	K	K
Reading	Water Leve	C.F.	Time (min)	(min)	(hr)	(cm3/hr)	(cm/hr)	(in/hr)	gal/ft2/day
43			0.0						
41			1.0						
39	2.0	105.0	2.0	1.00	0.017	12600.0	14.3165	5.6364	84.330
37	2.0	105.0	3.0	1.00	0.017	12600.0	14.3165	5.6364	84.330
35	2.0	105.0	4.0	1.00	0.017	12600.0	14.3165	5.6364	84.330
32.5	2.5	105.0	5.0	1.00	0.017	15750.0	17.8956	7.0455	105.412
21.5	11.0	105.0	10.0	5.00	0.083	13860.0	15.7481	6.2000	92.763
11	10.5	105.0	15.0	5.00	0.083	13230.0	15.0323	5.9182	88.546
0	11.0	105.0	20.0	5.00	0.083	13860.0	15.7481	6.2000	92.763
Commission of the last				- William		Final Ksat	15.510	6.106	91.357

SATURATED HYDRAULIC CONDUCTIVITY STUDY

Big Box LLC

Date: ####### 12/12/24 Weather Condition: Location: SB-3 Conetoe Temperature (F):

Number: Ksat 3

Horizon: C

cm in SET UP Depth(inches): 30.0 H20 42" Target Water Level: 15.2 6.0 eginning Water Level: cm 10.2 4.0 Ending Water Level: 10.2 4.0

Hole Depth: 76.2 30.0 Reference: 10.2 4.0 Head: 15.2 6.0

CHT Tube(s) setting: 71.1 28.0 Hole diameter (d): 5.0 cm

> Hole radius (r): 2.5 cm

Valve Setting: X coefficient A: 0.002045 1-ON 2-ON

NOTE: Readings based on Ending Water Level

sunny

45

Coversion Factor (C.F.): 105.0

Water	Change in	Chamber	Clock	Elapse	ed Time	Q	K	K	K
Reading	Water Leve	C.F.	Time (min)	(min)	(hr)	(cm3/hr)	(cm/hr)	(in/hr)	gal/ft2/day
46.5			0.0						
38			2.0						
27.5	10.5	105.0	5.0	3.00	0.050	22050.0	45.0921	17.7528	265.610
23.5	4.0	105.0	6.0	1.00	0.017	25200.0	51.5338	20.2889	303.555
19	4.5	105.0	7.5	1.50	0.025	18900.0	38.6504	15.2167	227.666
16.5	2.5	105.0	8.0	0.50	0.008	31500.0	64.4173	25.3611	379.443
13	3.5	105.0	9.0	1.00	0.017	22050.0	45.0921	17.7528	265.610
9	4.0	105.0	10.0	1.00	0.017	25200.0	51.5338	20.2889	303.555
0	9.0	105.0	12.5	2.50	0.042	22680.0	46.3805	18.2600	273.199
						Final Ksat	47.669	18.767	280.788

	BURING WAR	SEASONAL HIGH WATER TABLE WATER DEPTH	SERSONAL HIGH WATER TORCK ELEVATIONAUC)	STATIC WATER TABLE DEPH	Statu water Table Elevation	KSAT PATE	Kar Depth	Ksar trevanos
	1 7.341	22"	5.51	NE	NL	0.5" HOUR	32"	4.67'
	2 7.74	2011	6.06'	NE	NL	NR	_	4.65'
	3 7.32'	30 ^u	4.82	47"	3.403	18" HOUR	32"	
	4 7.291	30"	4.29	42"	3.79	P Mont	30 ¹¹	4.79
147 3.66 H20 EDGE	119 -8.39 -8	219 5.32 SNAIL 314 7.74 BORE B2 112 1130re-b2 7.58 7.58 I	312 7-7-34 1-7-7-34 1-7-7-34	1 (32") 0.5" Have	253 -253 -253 	95 -7.25 -5NAIL		311 7.29 BORE GS 1-507 2 (30") (4.29") 6" HORE HZO (3.79")

ATTACHMENT D - STORMWATER MANAGEMENT CALCULATIONS

- NCDEQ 1.5 Inch Post-Development Infiltration Basin Design Calculations
- Currituck 2 yr-24 hr Wooded Pre-Development Rational Method Calculations
- Currituck 5 Yr-24 hr Post-Development Rational Method Calculations
- Currituck Storage Volume and Drawdown Calculations
- 10 Yr -24hr Post-Development EPA SWMM Model Results

NCDEQ – 1.5 INCH INFILTRATION BASIN DESIGN CALCULATIONS

Commercial Site Development

Stormwater Management Calculations

Stormwater	Management	Calculations
------------	-------------------	--------------

First Flush Design Storm Rainfall Depth (R_{D1.5}) 1.50 in.

Total Drainage Area #1A

On-site Drainage Area	<i>45,328</i> s.f. or	1.04 ac.
Off-Site Drainage Area	<i>1,032</i> s.f. or	0.02 ac.
Total Drainage Area (A post)	<i>46,360</i> s.f. or	1.06 ac.

Soils Data

Soil TypeConetoe Loamy SandHydraulic Conductivity Rate, K18 in/hr.Seasonal High Water Table Elev.4.9 ft. msl

Soils Data Based On-Site Evaluation Performed by Protocol Sampling Service, Inc.

Built-Upon Area within Drainage Area #1A

Built Upon Area Description	Area (ft ²)	Factor	Adjusted Area (ft ²)	Acre
Proposed Building	9,608	1.0	9,608	0.22
Proposed Loading Area Canopy	2,322	1.0	2,322	0.05
Proposed Concrete Parking & Driveway	11,598	1.0	11,598	0.27
Proposed Concrete Dumpster & Generator Pads	205	1.0	205	0.00
Proposed Gravel Access Road	1,500	1.00	1,500	0.03
Total Built Upon Area			25,233	0.58

Runoff	Volume	Calculation	- Simple	Method
TANTOTE	1 OIGHIC	Calculation	- Dimpi	> INTERTACE

Region volume Carculation - Simple Method		
Post-Dev. Impervious Fraction (I _A)	0.54	54%
Post-Dev. Runoff Coeefficient (Rv post) = $0.05 + 0.9*(I_A)$	0.54	
First Flush Runoff Volume $(V_{1.5}) = 3630*R_{D1.5}*Rv_{post}*A_{post}$	3,128	ft ³
SCM Storage Volume Calculation		
Basin Bottom Elevation	6.9	ft. msl
Project Program Association	7.000	c.2

Basin Bottom Elevation	6.9	tt. msl
Basin Bottom Area	7,098	ft^2
Elevation @ Design Storm Storage Volume	7.40	ft. msl
Area of Basin @ Design Storm Storage Volume	7,605	ft^2
Depth of Basin @ Design Storm Storage Volume	0.50	ft
Design Storm Storage Volume Provided	3,676	ft^3
StorageVolume Provided>Storage Volume Reg'd	O.K.	

Drawdown Calculations

Drawdown Time, $T=FS*(Dv*12)/(K*SA)$		
Factor of Safety, FS	2	
Design Storage Volume Provided, Dv	3,676	ft^3
Surface Area of Bottom of Infiltration Basin, SA	7,098	ft^2
Hydraulic Conductivity Rate, K	18.0	in/hr
Drawdown Time (Hours)	0.69	hrs
Drawdown Period is < 72 hours	O.K.	


CURRITUCK – 2 YR-24 HR WOODED PRE-DEVLOPMENT RATIONAL METHOD CALCULATIONS


Rational Method Calculator

Big Box, LLC

Pre-Construction (Wooded, 2-yr, 24 hr rainfall event)

Curr SW Manual Sec 2.4.3.A, Rational Method





Time of Concentration:

Sheet Flow		
Mannings n =	0.1	(Woods, Table2-4)
Elev Up =	7.94	
Elev Down =	7.44	
Length =	300	
Slope =	0.001667	ft/ft
Tc ₁ =	41.23	min

Shallow Concentrated Flow

Land Use =	Unpaved		•
Elev. Up =	7.44		
Elev. Down =	6.87		
Length =	125	ft	
Slope =	0.00456	ft/ft	
Velocity =	55.84	fpm	(=972xS^0.53)
Tc ₂ =	2.24	min	(=L/V)

Channel Flow

Total Time of Concentration

Total Tc =
$$43.60 \text{ min}$$
 (=Tc₁+Tc₂+Tc₃)

Peak Flow Calculation:

Intensity, I =
$$\frac{2.33}{\text{in/hr}}$$
 (2 yr, Interpolated from Table 2-5)
 $Q_2 = \frac{0.56}{\text{cfs}}$ (Q=CiA)

Rational Method Calculator

Big Box, LLC

Post-Construction (5-yr, 24 hr rainfall event)

Curr SW Manual Sec 2.4.3.A, Rational Method

Composite C Calculation:

Table 2-2

Coverage	С	Area	Weighted Area
Impervious	0.95	0.61	0.5795
Open Space	0.25	0.66	0.17

Time fo Concentration:

Total Tc = 5.00 min

(Conservative assumption based on experience with

"= Input"
"= Calculated"

similar small commercial sites)

Peak Flow Calculation:

Intensity, I = 6.72 in/hr

(5yr, Interpolated from Table 2-5)

$$Q_5 = 5.00 \text{ cfs}$$

(Q=CiA)


CURRITUCK – STORAGE VOLUME AND DRAWDOWN CALCULATIONS

Runoff Depth Calculator

Big Box, LLC

Post-Construction (5-yr, 24 hr rainfall event)

Curr SW Manual Sec 2.4.3.B, (Steps 2 & 3)



Composite Cn Calculation:

Coverage	Cn	Area	Weighted Area
Impervious (A Soils)	98	0.61	59.78
Open Space (A Soils)	49	0.66	32.34

Composite Cn = 72.54


Calculate Runoff Depth:

Storage Volume Required Calculator

Big Box, LLC

Pre /Post -Construction (2-yr / 5yr, 24 hr mitigation)

Curr SW Manual Sec 2.4.4



Summary from other calculations:

Drainage Area =
$$\begin{array}{c} 1.27 \text{ ac.} \\ Q_2(\text{pre}) = \\ Q_5(\text{post}) = \\ Q(\text{Depth}) = \\ \end{array}$$

Calculate Runoff Volume:

$$(Vr = Q_{depth}/12*A)$$

Calculate Required Storage Volume:

$$(Vs = 1613.33 * Vr * (1 - Q2/Q5)$$

Vs = 8,392 cf

Calculate Storage Volume Provided:

Basin Bottom Area = 7,098 sf
Basin Bottom Elev. = 6.90 ft
Basin Top Area = 8,770 sf
Basin Top Elev. = 8.50 ft
Total Volume = 12,694 cf

Estimated 5yr Stage = 8.0 ft
Basin Area @ 5yr Stage = 8,232 sf
Basin Volume @ 5yr Stage = 8,432 cf

Infiltration Calculator

Big Box, LLC

Infiltration System Drawdown Calculations

NCDEQ SCM Manual

"= Input"
"= Calculated"

Summary of calculation:

Equation, T = FS * (Dv * 12)/(K * SA)

T = Dewatering (drawdown) Time (hrs)

FS = Factor of Safety

Dv = Design Volume (cf)

K = Hydraulic Conductivity (in/hr)

SA = Surface Area of bottom of infiltration basin (SF)

Calculate Drawdown time:

10 YR-24 HR POST-DEVELOPMENT EPA SWMM MODEL RESULTS

EPA STORM WATER MANAGEMENT MODEL - VERSION 5.1 (Build 5.1.014) ***********************************
************** NOTE: The summary statistics displayed in this report are based on results found at every computational time step, not just on results from each reporting time step. ***********************************
NOTE: The summary statistics displayed in this report are based on results found at every computational time step, not just on results from each reporting time step. ***********************************
Analysis Options
Flow Units

********	Volume	Depth
Runoff Quantity Continuity	acre-feet	inches

Total Precipitation	1.425	5.740
Evaporation Loss	0.000	0.000
Infiltration Loss	0.726	2.922
Surface Runoff	0.690	2.779
Final Storage	0.011	0.043
Continuity Error (%)	-0.084	
*******	Volume	Volume
Flow Routing Continuity	acre-feet	10^6 gal

Dry Weather Inflow	0.000	0.000
Wet Weather Inflow	0.691	0.225
Groundwater Inflow	0.000	0.000
RDII Inflow	0.000	0.000
External Inflow	0.000	0.000
External Outflow	0.440	0.143
Flooding Loss	0.000	0.000
Evaporation Loss	0.000	0.000
Exfiltration Loss	0.000	0.000
Initial Stored Volume	0.000	0.000
Final Stored Volume	0.251	0.082
Continuity Error (%)	-0.022	

Node SW-02 (12.53%)

Node SW-06 (2.50%)

Node CB-02 (1.72%)

Node CB-03 (1.11%)

None

All links are stable.

Routing Time Step Summary ************

Percent Not Converging

Minimum Time Step : 0.04 sec
Average Time Step : 0.67 sec
Maximum Time Step : 0.67 sec
Percent in Steady State : -0.00
Average Iterations per Step : 2.00

0.00

Subcatchment	Total Precip in	Total Runon in	Total Evap in	Total Infil in	Imperv Runoff in	Perv Runoff in	Total Runoff in	Total Runoff 10^6 gal	Peak Runoff CFS	Runoff Coeff
DA-04	 5.74	0.00	0.00	0.43	5.32	0.00	5.32	0.01	0.40	0.926
DA-03	5.74	0.00	0.00	0.67	5.07	0.00	5.07	0.02	0.47	0.884
DA-02	5.74	0.00	0.00	0.70	5.03	0.00	5.03	0.02	0.51	0.877
DA-01	5.74	0.00	0.00	0.46	5.28	0.00	5.28	0.01	0.40	0.920
DA-OF-4	5.74	0.00	0.00	2.10	0.00	3.59	3.59	0.04	1.62	0.626
DA-07	5.74	0.00	0.00	3.36	0.00	2.36	2.36	0.01	0.34	0.412
DA-OF-1	5.74	0.00	0.00	2.97	0.00	2.73	2.73	0.05	1.78	0.475
DA-OF-6	5.74	0.00	0.00	5.69	0.00	0.00	0.00	0.00	0.00	0.000
DA-OF-3	5.74	0.00	0.00	5.69	0.00	0.00	0.00	0.00	0.00	0.000
DA-06	5.74	0.00	0.00	2.92	0.00	2.78	2.78	0.01	0.59	0.485
DA-OF-2	5.74	0.00	0.00	2.30	0.00	3.39	3.39	0.04	1.48	0.591
DA-05	5.74	0.00	0.00	5.69	0.00	0.00	0.00	0.00	0.00	0.000
DA-SCM	5.74	0.00	0.00	5.69	0.00	0.00	0.00	0.00	0.00	0.000
DA-OF-5	5.74	0.00	0.00	2.40	0.00	3.29	3.29	0.01	0.50	0.573
DA-08	5.74	0.00	0.00	2.53	0.00	3.16	3.16	0.00	0.18	0.551

		Average	Maximum	Maximum	Time	of Max	Reported
		Depth	Depth	HGL	0ccu	rrence	Max Depth
Node	Type	Feet	Feet	Feet	days	hr:min	Feet
SW-15	JUNCTION	0.03	0.80	5.30	0	12:14	0.80
SW-14	JUNCTION	0.03	0.65	5.40	0	12:14	0.65
SW-07	JUNCTION	0.02	0.67	6.32	0	12:13	0.67
CB-04	JUNCTION	1.13	1.23	8.18	3	04:09	1.23
CB-03	JUNCTION	1.09	1.18	8.18	3	03:59	1.18
CB-02	JUNCTION	1.04	1.13	8.18	3	09:51	1.13
CB-01	JUNCTION	0.99	1.08	8.18	5	03:41	1.08
SW-09	JUNCTION	0.03	0.64	5.83	0	12:14	0.64
SW-08	JUNCTION	0.01	0.46	6.06	0	12:13	0.46
SW-02	JUNCTION	0.82	0.90	8.18	3	08:43	0.90
SW-13	JUNCTION	0.02	0.93	5.83	0	12:14	0.93
SW-01	JUNCTION	0.62	0.68	8.18	4	01:24	0.68
SW-05	JUNCTION	0.00	0.03	6.33	0	12:13	0.02
SW-06	JUNCTION	0.01	0.48	6.33	0	12:13	0.47
SW-10	JUNCTION	0.03	0.66	6.66	0	12:12	0.65
SW-11	JUNCTION	0.02	0.90	6.30	0	12:15	0.90
SW-12	JUNCTION	0.03	0.77	6.07	0	12:16	0.77
SW-04	JUNCTION	0.00	0.00	7.00	0	00:00	0.00
Outfall1	OUTFALL	0.04	0.80	4.80	0	12:14	0.80
SCM	STORAGE	1.17	1.28	8.18	5	01:14	1.28

Maximum	Maximum		Lateral	Total	Flow
Lateral	Total	Time of Max	Inflow	Inflow	Balance

		Lateral	Total	Time of Max	Inflow	Inflow	Balance
		Inflow	Inflow	Occurrence	Volume	Volume	Error
Node	Туре	CFS	CFS	days hr:min	10^6 gal	10^6 gal	Percent

SW-15	JUNCTION	0.50	4.77	0	12:14	0.0125	0.143	0.000
SW-14	JUNCTION	0.00	4.35	0	12:14	0	0.131	0.001
SW-07	JUNCTION	1.62	1.62	0	12:12	0.044	0.0447	-0.042
CB-04	JUNCTION	0.40	1.78	0	12:12	0.013	0.0635	0.923
CB-03	JUNCTION	0.47	1.38	0	12:12	0.0151	0.0499	1.127
CB-02	JUNCTION	0.51	0.91	0	12:12	0.0164	0.0329	1.751
CB-01	JUNCTION	0.40	0.40	0	12:12	0.0129	0.014	1.971
SW-09	JUNCTION	0.00	3.07	0	12:15	0	0.0922	-0.049
SW-08	JUNCTION	0.00	1.48	0	12:13	0	0.044	-0.011
SW-02	JUNCTION	0.34	0.92	0	12:12	0.00709	0.0223	14.323
SW-13	JUNCTION	1.48	4.37	0	12:14	0.0387	0.131	-0.002
SW-01	JUNCTION	0.59	0.59	0	12:12	0.0129	0.0144	8.539
SW-05	JUNCTION	0.00	0.01	0	12:11	0	3.95e-06	0.031 ga
SW-06	JUNCTION	0.00	0.13	0	12:06	0	0.000723	2.566
SW-10	JUNCTION	1.78	1.78	0	12:12	0.0482	0.0482	-0.202
SW-11	JUNCTION	0.00	1.73	0	12:12	0	0.0483	0.203
SW-12	JUNCTION	0.00	1.62	0	12:15	0	0.0483	0.110
SW-04	JUNCTION	0.00	0.00	0	00:00	0	0	0.000 ga
Outfall1	OUTFALL	0.00	4.77	0	12:14	0	0.143	0.000
SCM	STORAGE	0.18	2.84	0	12:12	0.0043	0.0817	1.926

Node Surcharge Summary **********

No nodes were surcharged.

No nodes were flooded.

	Average	Avg	Evap E	Exfil	Maximum	Max	Time of Max	Maximum
	Volume	Pcnt	Pcnt	Pcnt	Volume	Pcnt	Occurrence	Outflow
Storage Unit	1000 ft3	Full	Loss	Loss	1000 ft3	Full	days hr:min	CFS
SCM	9.091	19	0	0	9.932	20	5 01:14	0.01

Outfall Node	Flow Freq Pcnt	Avg Flow CFS	Max Flow CFS	Total Volume 10^6 gal
Outfall1	10.40	0.34	4.77	0.143
System	10.40	0.34	4.77	0.143

Link	Type	Maximum Flow CFS	0ccu	of Max rrence hr:min	Maximum Veloc ft/sec	Max/ Full Flow	Max/ Full Depth
SW15-Outfall1	CONDUIT	4.77	0	12:14	2.48	0.05	0.32
SW14-SW15	CONDUIT	4.34	0	12:14	2.75	0.03	0.29
P-04	CONDUIT	1.77	0	12:12	2.65	0.95	0.99
P-03	CONDUIT	1.37	0	12:12	1.55	0.67	0.96
P-02	CONDUIT	0.91	0	12:12	1.01	0.47	0.92
P-01	CONDUIT	0.40	0	12:12	0.46	0.20	0.88
SW08-SW09	CONDUIT	1.48	0	12:13	1.91	0.04	0.37
P-06	CONDUIT	1.48	0	12:13	2.41	0.41	0.38
SW02-SW03	CONDUIT	0.89	0	12:12	1.08	0.05	0.73
SW1-DI2	CONDUIT	0.58	0	12:12	0.73	0.07	0.53
P-07	CONDUIT	4.35	0	12:14	3.75	0.32	0.40
SW09-SW13	CONDUIT	3.16	0	12:16	1.81	0.02	0.32

SW04-SW05	CONDUIT	0.00	0	00:00	0.00	0.00	0.01
P-05	CONDUIT	0.01	0	12:11	0.04	0.00	0.21
SW06-SW07	CONDUIT	0.13	0	12:06	0.21	0.02	0.39
SW10-SW11	CONDUIT	1.73	0	12:12	1.14	0.11	0.52
EX-PIPE	CONDUIT	1.62	0	12:15	1.85	0.96	0.67
SW12-SW09	CONDUIT	1.61	0	12:15	1.12	0.09	0.35
OVERFLOWWEIR	WEIR	0.00	0	00:00			0.00

	Adjusted			Fract	ion of	Time	in Flo	w Clas	s	
	/Actual		Up	Down	Sub	Sup	Up	Down	Norm	Inlet
Conduit	Length	Dry	Dry	Dry	Crit	Crit	Crit	Crit	Ltd	Ctrl
SW15-Outfall1	1.00	0.07	0.00	0.00	0.93	0.00	0.00	0.00	0.87	0.00
SW14-SW15	1.00	0.07	0.00	0.00	0.93	0.00	0.00	0.00	0.17	0.00
P-04	1.00	0.00	0.00	0.00	1.00	0.00	0.00	0.00	0.00	0.00
P-03	1.00	0.00	0.00	0.00	1.00	0.00	0.00	0.00	0.00	0.00
P-02	1.00	0.00	0.00	0.00	1.00	0.00	0.00	0.00	0.00	0.00
P-01	1.00	0.00	0.00	0.00	1.00	0.00	0.00	0.00	0.04	0.00
SW08-SW09	1.00	0.07	0.00	0.00	0.93	0.00	0.00	0.00	0.92	0.00
P-06	1.00	0.07	0.81	0.00	0.11	0.00	0.00	0.00	0.84	0.00
SW02-SW03	1.00	0.00	0.08	0.00	0.92	0.00	0.00	0.00	0.00	0.00
SW1-DI2	1.00	0.08	0.00	0.00	0.92	0.00	0.00	0.00	0.00	0.00
P-07	1.00	0.07	0.75	0.00	0.17	0.00	0.00	0.00	0.88	0.00
SW09-SW13	1.00	0.07	0.00	0.00	0.90	0.02	0.00	0.00	0.03	0.00
SW04-SW05	1.00	1.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
P-05	1.00	0.08	0.92	0.00	0.00	0.00	0.00	0.00	0.92	0.00
SW06-SW07	1.00	0.07	0.00	0.00	0.92	0.00	0.00	0.00	0.91	0.00
SW10-SW11	1.00	0.08	0.00	0.00	0.92	0.00	0.00	0.00	0.04	0.00
EX-PIPE	1.00	0.07	0.81	0.00	0.12	0.00	0.00	0.00	0.84	0.00
SW12-SW09	1.00	0.07	0.00	0.00	0.93	0.00	0.00	0.00	0.81	0.00

Conduit				Hours Above Full Normal Flow	Capacity
P-04	0.01	0.01	128.00	0.01	0.01

Analysis begun on: Thu Jan 23 13:53:18 2025 Analysis ended on: Thu Jan 23 13:53:25 2025 Total elapsed time: 00:00:07

ATTACHMENT E — SEDIMENTATION AND EROSION CONTROL CALCULATIONS

- Erosive Velocity Calculations
- Sediment Basin Calculations

EROSIVE VELOCITY CHECK

Calculations Include the Following:

- 2 Year, Bare Soil Condition; 2 fps Max Velocity
- 10 Year, Vegetated Condition; 4 fps Max Velocity

Note: This check is performed by highlighting respective summaries of conveyances that exceed maximum permissible velocities as determined by separate EPA SWMM modeling.

Link Flov	w and Velocity -	2yr	Velocity Check
Link	Flow (cfs)	Velocity (fps)	Bare Soil > 2 fps
SW15-Outfall1	1.49	1.85	OK
SW14-SW15	1.30	2.07	SPEC LINER
P-04	1.14	2.73	PIPE, OK
P-03	0.89	1.41	OK
P-02	0.59	0.92	OK
P-01	0.26	0.44	OK
SW08-SW09	0.69	1.98	OK
P-06	0.69	1.78	OK
SW02-SW03	0.17	0.5	OK
SW1-DI2	0.19	0.61	OK
P-07	1.30	2.48	PIPE, OK
SW09-SW13	0.82	1.61	OK
SW04-SW05	0.00	0.00	OK
P-05	0.00	0.00	OK
SW06-SW07	0.07	0.25	OK
SW10-SW11	0.35	0.86	OK
EX-PIPE	0.34	0.90	OK
SW12-SW09	0.34	0.71	OK
OVERFLOWWEIR	0.00	0.00	OK

^{*}Estimated peak flows and velocities per EPA SWMM model results

Link Flow and Velocity - 10yr					
Link	Flow (cfs)	Velocity (fps)			
SW15-Outfall1	4.77	2.48			
SW14-SW15	4.34	2.75			
P-04	1.77	2.65			
P-03	1.37	1.55			
P-02	0.91	1.01			
P-01	0.40	0.46			
SW08-SW09	1.48	1.91			
P-06	1.48	2.41			
SW02-SW03	0.89	1.08			
SW1-DI2	0.58	0.73			
P-07	4.35	3.75			
SW09-SW13	3.16	1.81			
SW04-SW05	0.00	0.00			
P-05	0.01	0.04			
SW06-SW07	0.13	0.21			
SW10-SW11	1.73	1.14			
EX-PIPE	1.62	1.85			
SW12-SW09	1.61	1.12			
OVERFLOWWEIR	0.00	0.00			

Velocity Check
Vegetated > 4 fps
OK

^{*}Estimated peak flows and velocities per EPA SWMM model results

Sediment Basin 1

Requirements		
Tributary Disturbed Area*	1.06	acres
Min. Required Storage Volume	1,908	$\frac{1}{}$ ft 3 (1,800 ft 3 /acre)
Estimated 10 year peak inflow**	2.84	cfs
Min. Required Surface Area	1,235	$ft^2 \qquad (435 ft^2/cfs)$
<u>Design</u>		
Choose Avg. Storage Depth	1.5	ft
Necessary Storage Surface Area	1,272	-ft ²
Is Necessary Surface Area > Required	YES	
Choose Storage Width	80	ft
Choose Storage Length	110	ft
Length to Width Ratio	1.4	Ratio Not Met
Surface Area Provided	8,770	ft ² 7.1 times required
Is Surface Area Provided > Required	YES	
Storage Volume Provided	12,694	ft^3
Is Storage Volume Provided > Required	YES	6.7 times required

The temporary sediment basin will ultimately be utilized as a stormwater infiltration basin. Drawdown calculations resolve that the basin's full capacity volume will infiltrate into the site's excessivly drained soils in a period of approximately 2.30 hours. For this reason, no formal drawdown devices are provided.

^{*} Tributary Disturbed Area from Autocad

^{**} Estimated 10 year peak flows per separate EPA SWMM calculations

ATLANTIC ENVIRONMENTAL CONSULTANTS, LLC

PO Box 3266, Kitty Hawk, NC 27949

January 31, 2025

Dave Klebitz Bissell Professional Group 3512 N. Croatan Hwy Kitty Hawk, NC 27949

RE: Site Evaluation - Parcel ID. No.012500000010000

Dear Mr. Klebitz,

This letter pertains to a site evaluation conducted on January 31, 2025, for the parcel located on Caratoke Highway in Poplar Branch, Currituck County, North Carolina.

The site was assessed for the presence of wetlands subject to Section 404 of the Clean Water Act. Atlantic Environmental Consultants, LLC conducted the evaluation using the 1987 U.S. Army Corps of Engineers Wetland Delineation Manual. Based on our assessment, no hydric soils or wetland hydrology were identified within the parcel boundaries. Therefore, the site does not meet the criteria for jurisdictional wetlands under Section 404 of the Clean Water Act, as regulated by the U.S. Army Corps of Engineers.


For reference, the attached survey from Bissell Professional Group, dated January 13, 2025, outlines the property review area.

Sincerely,

Doug Dorman

Atlantic Environmental Consultants, LLC

Cell: (252) 599-2603 Office: (252) 261-7707 Email: dougdaec@gmail.com





Rational Method Peak Flow Form SW-003

Project Information		
Project Location: <u>CARATOKE HIGHWAY</u>	HARB	INGET
Parcel Identification Number(s): <u>CIZS -600</u>	00-000	21-000
Drainage area:	ac	SEE PRE & FOST DEVELOPMENT
Average Slope:	<u>%</u>	PATIONIAL METHLO CALCULATIONS
Maximum Slope Length:	<u>ft</u>	SEE PRE & FOST DEVELOPMENT RATIONAL METHOD CALCULATIONS UNDER ATTACHMENT D'OF STORM BEFORT

Calculations

^{*}The Rational Method may only be used where development will impact less than 10 acres

Time of Concentration (Tc) (Use additional sheets if necessary)			
(ose additional sheets if flecessary)	Pre-	Post-	
Sheet Flow			
Manning's roughness, n (Table 2-4)			
2-year, 24-hour Rainfall, P	4.0	6.0	in
Slope, S			ft/ft
Length of Sheet Flow, L (<=300 feet)			ft
Total Time for Sheet Flow			min
Shallow Concentrated Flow			
Surface Paved (P) or Unpaved (U)			
Length of flow, L			ft
Slope, S			ft/ft
Average Velocity, V (Table 2-3)			ft/min
Total Time for Shallow Concentrated Flow			min
<u>Channel Flow</u>			
Pipe (P) or Channel (C)			
If pipe: Diameter, D			in
lf channel: Bottom Width, w			ft
If channel: side slope 1 (:1)			
If channel: side slope 2 (:1)			
Cross sectional flow area, A			sq ft
Wetted perimeter, Wp			ft
Hydraulic radius, R = A/Wp			ft

	Pre-	Post-		
Channel slope, S			ft/ft	
Manning's roughness, n (Table 2-4)				
Channel velocity			ft/sec	
Length of Flow, L			ft/sec	
Total Time for Channel Flow			min	
Total Time of Concentration, Tc			min	
Pre-development Conditions				
Land Use Description	С	Area (acres)	C*A	
Woods	0.2			
Total				
) 7 7		
ntensity for 2-year, 24-hour storm (Table 2-5)		4.5>	in/hr	
Pre-development peak flow, Q = CiA	2.33 0.56		cfs	
Post-development Conditions				
and Use Description	С	Area (acres)	C*A	
Totals				
area-weighted C:		0.59	_	
ntensity for 10-year, 24-hour storm (Table 2-5)		0.72	_ in/hr	
		5.00	_ cfs	See
ost-development peak tlow, Q = CiA				
	on 2.4.4 for	Volume Calcula	ations	UM
Post-development peak flow, Q = CiA Minimum Storage Volume Required - Refer to Section Storage Volume, Vs	***	3.392	tions _ ft3 cwinico / 31/25	AFFA

ALBEMARLE REGIONAL HEALTH SERVICES

Applicant:

Big Box LLC c/o Monica Thibodeau 1197 Duck Rd Duck, NC 27949

Owner:

Big Box LLC c/o Monica Thibodeau 1197 Duck Rd Duck, NC 27949

Site Location:

8760 Caratoke Hwy Harbinger, NC 27941

GPD: 500 LTAR: 0.500 Classification:

If unsuitable, the site may be reclassified to provisionally suitable with the following modification(s):

* Other: Seasonal Soil Wetness was found to be at 20", therefore, 16" of sand fill above existing (original, prior to removal of trees) grade will be needed.

To obtain an Authorization to Construct:

- * Submit a plat or scale drawing of the lot, showing location and dimensions of all property lines, proposed structures and driveways
- * Pay permit fee of \$735

Comments:

- **Seasonal Soil Wetness @ 20"
- **A benchmark elevation should be established prior to clearing of trees so original grade in known.
- **Finished building pad to be higher than finished septic tank grade, unless a pump is used

EHS:

Carver, Kevin

Date: 10/30/2024

THIS APPROVAL WILL BECOME VOID AFTER 12 MONTHS AND A NEW APPLICATION WILL BE NECESSARY.

Check if this project is ARPA-funded	
Attach a copy of the Letter of Intent to Fund	

FINANCIAL RESPONSIBILITY/OWNERSHIP FORM SEDIMENTATION POLLUTION CONTROL ACT

No person may initiate any land-disturbing activity on one or more acres as covered by the Act, including any activity under a common plan of development of this size as covered by the NCG01 permit, before this form and an acceptable erosion and sedimentation control plan have been completed and approved by the Land Quality Section, N.C. Department of Environmental Quality. Submit the completed form to the appropriate Regional Office. (Please type or print and, if the question is not applicable or the e-mail address or phone number is unavailable, place N/A in the blank.)

num	ber is unavailabl	ie, place N/A in tr	ne blank.)			
Parl						
1.	Project Name_	Big Box, LL	C Comme	rcial Site	Development	<u>t</u>
	Number		RP-0121) belov			Project Name or Project I for funding through the
2.	Location of lan	d-disturbing activ	rity: County C	urrituck	City or Townsh	_{hip} Harbinger
	Highway/Stree	tUS HWY 1	58 Latitu	Ide(decimal degrees	36.09861 Longitud	
3.	Approximate d	ate land-disturbir	ng activity will c	ommence: 4/	1/25	
4.					institutional, etc.):_	Commercial
5.	Total acreage	disturbed or unco	vered (includin	g off-site born	ow and waste areas	3):_1.50
6.	Amount of fee	m c	200 d without a ceil			00.00 per acre (rounded application fee is \$900)
7.	Has an erosion	and sediment c	ontrol plan bee	n filed? Yes [☐ Enclosed ☑	No 🗆
8.	Person to cont	act should erosio	n and sedimen	t control issue	s arise during land-	disturbing activity:
	Name Ryan	Thibodeau		F-mail Add	ess ryan.thibodeau	@carolinadesigns.com
			3934	Mobile # 2	252-202-2988	
9.	I andowner(s)	of Record (attach	accompanied	nage to list ad	ditional owners):	
0.	Big Box, I		doornpanioa	252-26		252-207-7739
	Name			Phone: Off	ice #	Mobile #
	1197 Duc	k Road		1197 D	uck Road	
	Current Mailing	Address		Current Stre	eet Address	
	Duck	NC	27949	Duck	NC	27949
	City	State	Zip	City	State	Zip
10.	Deed Book No	1554	Page No5	78	_Provide a copy of	the most current deed.

Part B.

1. Company(ies) who are financially responsible for the land-disturbing activity (Provide a comprehensive list of all responsible parties on accompanied page.) If the company is a sole proprietorship or if the landowner(s) is an individual(s), the name(s) of the owner(s) may be listed as the financially responsible party(ies).

Big Box,	LLC		monica.thib	odeau@carolina	designs.com
Company Nar	ne		E-mail Address		
1197 Due	Duck Road		1197 Duck Road		
Current Mailin	g Address		Current Street A	Address	
Duck	NC	27949	Duck	NC	27949
City	State	Zip	City	State	Zip
Phone: Office # 252-261-3934			Mobile # 252-207-7739		

Note: If the Financially Responsible Party is not the owner of the land to be disturbed, include with this form the landowner's signed and dated written consent for the applicant to submit a draft erosion and sedimentation control plan and to conduct the anticipated land disturbing activity.

2. (a) If the Financially Responsible Party is a domestic company registered on the NC Secretary of State business registry, give name and street address of the Registered Agent:

Monica T	hibodeau		monica.thibo	deau@carolinade	signs.com			
Name of Registered Agent			E-mail Address					
1197 Duck Road			1197 Duck Road					
Current Mailin	g Address		Current Street Ad	dress				
Duck	NC	27949	Duck	NC	27949			
City	State	Zip	City	State	Zip			
Phone: Office	, _# _252-261-39	934	Mobile # 252-20	07-7739				
(b) If the Fina of the designation	ancially Responsible ated North Carolina	Party is not a agent who is	resident of North Ca registered on the NC	arolina, give name and Secretary of State busi	street address iness registry:			
Name of Regi	stered Agent		E-mail Address					
Current Mailin	g Address		Current Street Ad	dress				
City	State	Zip	City	State	Zip			
Phone: Office	÷#		Mobile #					

Name of Individual to Contact (if Registered Agent is a company)

Partnership, or other company not registered and of the Certificate of Assumed Name.	d doing business under an assumed name, attach a copy
Company DBA Name	
by me under oath. (This form must be signed by or his attorney-in-fact, or if not an individual, by	e best of my knowledge and belief and was provided the Financially Responsible Person if an individual(s) an officer, director, partner, or registered agent with Financially Responsible Party). I agree to provide ge in the information provided herein.
Monica Thibodeau	Agent, Managing Member
Type or print name	Title or Authority
Signature Signature	V 24/35 Date
1, Christy Hanks, a	Notary Public of the County of
State of North Carolina, hereby certify that	A) appeared personally ledged that the above form was executed by him/her.
Witness my hand and notarial seal, this 27	day of January, 2025
Christy Hanks NOTARY PUBLIC	Notary Maks
Dare County, NC My Commission Expires November 05, 2029	My commission expires NOWWbev 05, 2029

(c) If the Financially Responsible Party is engaging in business under an assumed name, give name under which the company is Doing Business As. If the Financially Responsible Party is an individual, General

Operation & Maintenance Agreement

Project Name: Big Box, LLC Commercial Site Development

Project Location: Harbinger, Currituck County, NC

Cover Page

Maintenance records shall be kept on the following SCM(s). This maintenance record shall be kept in a log in a known set location. Any deficient SCM elements noted in the inspection will be corrected, repaired, or replaced immediately. These deficiencies can affect the integrity of structures, safety of the public, and the pollutant removal efficiency of the SCM(s).

The SCM(s) on this project include (check all that	at apply & corr	esponding	O&M sheets will b	e added automatically):
Infiltration Basin	Quantity:	1	Location(s):	Rear of project
Infiltration Trench	Quantity:		Location(s):	
Bioretention Cell	Quantity:		Location(s):	
Wet Pond	Quantity:		Location(s):	
Stormwater Wetland	Quantity:		Location(s):	
Permeable Pavement	Quantity:		Location(s):	
Sand Filter	Quantity:		Location(s):	
Rainwater Harvesting	Quantity:		Location(s):	
Green Roof	Quantity:		Location(s):	
Level Spreader - Filter Strip	Quantity:		Location(s):	
Proprietary System	Quantity:		Location(s):	
Treatment Swale	Quantity:		Location(s):	
Dry Pond	Quantity:		Location(s):	
Disconnected Impervious Surface	Present:	No	Location(s):	
User Defined SCM	Present:	No	Location(s):	
Low Density	Present:	No	Type:	

I acknowledge and agree by my signature below that I am responsible for the performance of the maintenance procedures listed for each SCM above, and attached O&M tables. I agree to notify NCDEQ of any problems with the system or prior to any changes to the system or responsible party.

Responsible Party:	
Title & Organization:	
Street address:	1197 Duck Road
City, state, zip:	
Phone number(s):	252-261-393 <mark>4</mark>
Email:	monica.thibodeau@carolinadesigns.com

Signature: Date: 127/25 I, County of Dare , do hereby certify that Marica Thibodeau
personally appeared before me this 21 day of January 2025 and
acknowledge the due execution of the Operations and Maintenance Agreement . Witness my hand and official seal,
Christy Hanks NOTARY PUBLIC Dare County, NC My Commission Expires November 05, 2029
Seal My commission expires MINVEMBER 05, 2029

Infiltration Basin Maintenance Requirements

Important operation and maintenance procedures:

- The drainage area will be carefully managed to reduce the sediment load to the infiltration basin. No portion of the infiltration basin will be fertilized after the initial fertilization that is required to
- establish the vegetation. Lime may be allowed if vegetation is planted on the surface of the infiltration basin and a soil test shows that it is needed.
- The vegetation in and around the basin will be maintained at a height of four to six inches.

After the infiltration basin is established, it will be inspected quarterly and within 24 hours after every storm event greater than 1.0 inches (or 1.5 inches if in a Coastal County) . Records of operation and maintenance shall be kept in a known set location and shall be available upon request.

Inspection activities shall be performed as follows. Any problems that are found shall be repaired immediately.

SCM element:	Potential problem:	How to remediate the problem:
The entire infiltration basin	Trash/debris is present.	Remove the trash/debris.
The grass filter strip or	Areas of bare soil and/or erosive gullies have formed.	Regrade the soil if necessary to remove the gully, plant ground cover and water until it is established. Provide lime and a one-time fertilizer application.
other pretreatment area	Sediment has accumulated to a depth of greater than three inches.	Search for the source of the sediment and remedy the problem if possible. Remove the sediment and dispose of it in a location where it will not cause impacts to streams or the SCM.
The flow diversion	The structure is clogged.	Unclog the conveyance and dispose of any sediment in a location where it will not cause impacts to streams or the SCM.
structure (if applicable)	The structure is damaged.	Make any necessary repairs or replace if damage is too much for repair.
	The inlet pipe is clogged (if applicable).	Unclog the pipe and dispose of any sediment in a location where it will not cause impacts to streams or the SCM.
	The inlet pipe is cracked or otherwise damaged (if applicable).	Repair or replace the pipe.
The inlet device	Erosion is occurring in the swale (if applicable).	Regrade the swale if necessary and provide erosion control devices such as reinforced turf matting or riprap to avoid future erosion problems.
	Stone verge is clogged or covered in sediment (if applicable).	Remove sediment and clogged stone and replace with clean stone.
	More than four inches of sediment has accumulated.	Search for the source of the sediment and remedy the problem if possible. Remove the sediment and dispose of it in a location where it will not cause impacts to streams or the SCM.
The basin	Erosion of the basin surface has occurred or riprap is displaced.	Provide additional erosion protection such as reinforced turf matting or riprap if needed to prevent future erosion problems.
	Water is standing more than three days after a storm event.	Replace the top few inches of soil to see if this corrects the standing water problem. If not, consult an appropriate professional for a more extensive repair.

Infiltration Basin Maintenance Requirements (continued)					
SCM element:	SCM element: Potential problem: How to remediate the problem:				
	Shrubs or trees are growing on the embankment.	Remove shrubs and trees immediately.			
The embankment	An annual inspection by an appropriate professional shows that the embankment needs repair.	Make needed repairs immediately.			
The outlet device	Clogging has occurred.	Clean out the outlet device and dispose of sediment in a location where it will not cause impacts to streams or the SCM.			
	The outlet device is damaged	Repair or replace the outlet device.			
	Erosion or other signs of damage have occurred at the outlet.	Repair the damage and improve the flow dissipation structure.			
The receiving water	Discharges from the infiltration basin are causing erosion or sedimentation in the receiving water.	Contact the local NCDEQ Regional Office.			

DEMLR USE ONLY						
Date Received		Fee Paid			Permit Number	
Applicable Rules:	☐ Coastal SW -	1995	☐ Coastal SW -	- 2008	☐ Ph II - Post Construction	
(select all that apply)	☐ Non-Coastal	SW-HQW	//ORW Waters	☐ Univer	sal Stormwater Management Plan	
	☐ Other WQ M	gmt Plan:				

State of North Carolina Department of Environmental Quality Division of Energy, Mineral and Land Resources

F	POST-CONSTRUCTION STORMWATER MANAGEMENT PERMIT APPLICATION FORM This form may be photocopied for use as an original.
I.	GENERAL INFORMATION
1.	Project Name (subdivision, facility, or establishment name - should be consistent with project name on plans, specifications, letters, operation and maintenance agreements, etc.):
	Big Box, LLC Commercial Site Development
2.	Location of Project (street address):
	Caratoke Highway
	City: Harbinger County: Currituck Zip: 27941
3.	Directions to project (from nearest major intersection):
	The site is located along the west side of Caratoke Hwy (US HWY 158), approx. 170 ft north of its intersection
	with Hall Harbor Rd. (SR 1106)
	Э <u>————————————————————————————————————</u>
4.	Latitude: 36° 05′ 55″ N Longitude: -75° 48′ 47″ W of the main entrance to the project.
	PERMIT INFORMATION: a. Specify whether project is (check one): New Modification Renewal w/ Modification The Renewals with modifications also requires SWU-102 - Renewal Application Form a. If this application is being submitted as the result of a modification to an existing permit, list the existing permit number, its issue date (if known), and the status of construction: Not Started Partially Completed* Completed* *provide a designer's certification*
2.	Specify the type of project: □Low Density □ Drains to an Offsite Stormwater System □ Other
3.	If this application is being submitted as the result of a previously returned application or a letter from DEMLR requesting a state stormwater management permit application, list the stormwater project number, if assigned, and the previous name of the project, if different than currently proposed,
4.a	Additional Project Requirements (check applicable blanks; information on required state permits can be obtained by contacting the Customer Service Center at 1-877-623-6748):
	☐ CAMA Major ☐ Sedimentation/Erosion Control: 1.50 ac of Disturbed Area
	□NPDES Industrial Stormwater □404/401 Permit: Proposed Impacts
b	.If any of these permits have already been acquired please provide the Project Name, Project/Permit Number, issue date and the type of each permit:
5.	Is the project located within 5 miles of a public airport? No Yes If yes, see S. I. 2012-200, Part VI: http://portal.pcdepr.org/web/lr/rules-and-regulations

III. CONTACT INFORMATION

1.a.Print Applicant / Signing Official's name and title (spe designated government official, individual, etc. who o		per, property owner, lessee,
Applicant/Organization:Big Box, LLC		
Signing Official & Title:Monica Thibodeau, Registered	Agent, Managing	Member
b.Contact information for person listed in item 1a above	9 :	
Street Address:1197 Duck Road		
City:Duck	State:NC	Zip:27949
Mailing Address (<i>if applicable</i>):1197 Duck Road		
City:Duck	State:NC	Zip: <u>27949</u>
Phone: (252) 261-3934)
Email:monica.thibodeau@carolinadesigns.com		
c. Please check (one) the appropriate box. The applicat	item 3a) nd complete Conta greement and com	
2.a.Print Property Owner's name and title below, if you at person who owns the property that the project is local		haser or developer. (This is the
Property Owner/Organization:		
Signing Official & Title:		
b. Contact information for person listed in item 2a above	e :	
Street Address:		
City:	State:	Zip:
Mailing Address (if applicable):		
City:	State:	Zip:
Phone: ()	Fax: ()
Email:		
3.a. (Optional) Print the name and title of another contact person who can answer questions about the project:	such as the proje	ct's construction supervisor or other
Other Contact Person/Organization: Ryan Thibodeau		
Signing Official & Title: Marketing and Operations Man	nager at Carolina I	Designs Realty, Inc
b.Contact information for person listed in item 3a above	e :	
Mailing Address:1197 Duck Road		
City:Duck	State:NC	Zip: <u>27949</u>
Phone: (252) 261-3934	Fax: ()
Email:ryan.thibodeau@carolinadesigns.com		
4. Local jurisdiction for building permits: Currituck Count	ty	
Point of Contact: Bill Newns	Phone #: (252	2) 232-6023
Email: <u>bil.newns@currituckcountync.gov</u>		

IV. PROJECT INFORMATION

1,	In the space provided below, <u>briefly</u> summarize how the s Stormwater runoff from built-upon areas will be conveyed	torr	n a	water runoff will be treated. single infiltration basin for treatmer	nt & disposal
2.a	. If claiming vested rights, identify the supporting docume Approval of a Site Specific Development Plan or PUD Valid Building Permit Other:	ents	- F	provided and the date they were an Approval Date: Issued Date: Date:	
b	b. If claiming vested rights, identify the regulation(s) the p Coastal SW – 1995 Ph II – Post Construction	roje	cl	has been designed in accordance	
3.	Stormwater runoff from this project drains to the Pasquot	ank	<u> </u>		River basin.
4.	Total Property Area: 1.34acres			Total Coastal Wetlands Area: 0 Total Surface Water Area: 0	acres acres
7.	Total Property Area (4) – Total Coastal Wetlands Area (5 Area*: 1.34 acres				
	+ Total project area shall be calculated to exclude the following: the information of streams and rivers, the area below the Normal High Water (NHW landward from the NHW (or MHW) line. The resultant project area is coastal wetlands landward of the NHW (or MHW) line may be included.	') line s use	e d ed	or Mean High Water (MHW) line, and coast to calculate overall percent built upon area	ai wellarius
8.	Project percent of impervious area: (Total Impervious Area	a /	T	otal Project Area) X 100 = 46.81	%
9.	How many drainage areas does the project have? 1 (Follow density and other projects, use 1 for the whole proper provide the drainage areas within the project area to each	hig	gh ar	density, count 1 for each propose ea. If there are multiple receiving s	d SCM. For
	the state of the s				a identified in

10. Complete the following information for each drainage area directed to an SCM or low density area identified in Project Information item 9. If there are more than four drainage areas in the project, attach an additional sheet with the information for each area provided in the same format as below.

Basin Information	Drainage Area 1A	Drainage Area 1B	Drainage Area 2	Drainage Area 3
Receiving Stream Name	Currituck Sound	Currituck Sound	Currituck Sound	Currituck Sound
Stream Class *	SC	SC	SC	SC
Stream Index Number *	30-1	30-1	30-1	30-1
Total Drainage Area (sf)	46360	9984	1375	457
On-site Drainage Area (sf)	45328	9984	1375	457
Off-site Drainage Area (sf)	1032	0	0	0
Proposed Impervious Area** (sf)		1786	213	0
% Impervious Area** (total)	54.4%	17.9%	15.5%	0

Impervious** Surface Area	Drainage Area 1A	Drainage Area 1B	Drainage Area 2	Drainage Area 3
On-site Buildings/Lots (sf)	11930	0	0	0
	1500	979	213	0
On-site Streets (sf)	1	0.0	0	0
On-site Parking (sf)	11598	007	0	0
On-site Sidewalks (sf)	0	807	0	0
Other on-site (sf)	205	0	U	0
Future (sf)	0	0	0	0
Off-site (sf)	0	0	0	0
Existing BUA*** (sf)	0	0	0	0
Total (sf):	25233	1786	213	0

^{*} Stream Class and Index Number can be determined at: https://www.deq.nc.gov/about/divisions/water-resources/water-planning/classification-standards/classifications

** Impervious area is defined as the built upon area including, but not limited to, buildings, roads, parking areas, sidewalks, gravel areas, etc.

^{***} Report only that amount of existing BUA that will <u>remain</u> after development. Do not report any existing BUA that is to be removed and which will be replaced by new BUA. See definition 15A NCAC 02H .1002(17).

11.	How was the off-site impervious area listed the Section IV, 10 Tables determined? Provide doct N/A	umentation.
Thr	iects in Union County: Contact DEMLR Central Office staff to check if the project is located wit eatened & Endangered Species watershed that may be subject to more stringent stormwater red 15A NCAC 02B .0600.	thin a quirements as
٧.	SUPPLEMENT AND O&M FORMS	
from prosup	e applicable state stormwater management permit supplement and operation and maintenance (state submitted for each SCM specified for this project. The latest versions of the forms can be on https://www.deq.nc.gov/about/divisions/energy-mineral-and-land-land-land-land-land-land-lan	vater- i, the archived
VI.	CHECKLIST OF SUBMITTAL REQUIREMENTS FOR AN ADMINISTRATIVELY COMPLET APPLICATION PACKAGE PER 15A NCAC 02H .1042(2)	
Lar list http pro app ma	by complete application packages will be accepted and reviewed by the Division of Energy and Resources (DEMLR). An administratively complete application package includes all of ed below. A detailed application instruction sheet and SCM checklists are available from as://www.deg.nc.gov/about/divisions/energy-mineral-and-land-resources/stormwater/post-construction-permits-permit-modifications. The complete application package should be submoropriate DEMLR Office. (The appropriate office may be found by locating project on the interaction at https://www.deg.nc.gov/about/divisions/energy-mineral-and-land-resources/stormwater/storigram/post-construction-program .)	uction- itted to the ctive online
pro ver	ase <u>indicate that the following required information have been provided by initialing</u> in the vided for each item. All original documents MUST be signed and initialed in blue ink. Download sions for each submitted application package from https://www.deq.nc.gov/about/divisions/el-land-resources/stormwater/stormwater-program .	i the latest
		Initials
1. 2.	Original and one copy of the Stormwater Management Permit Application Form. Original and one copy of the signed and notarized Deed Restrictions & Protective Covenants Form or, for major modifications, a copy of the recorded deed restrictions and protective covenants limiting the built-upon area so that it does not exceed the capacity of the SCM(s) or the BUA thresholds. (if required as per Part VII below)	4/A
	Deed book: Page No: Relevant section:	PAK
3.	Original of the applicable Supplement Form(s) (sealed, signed and dated) and O&M agreement(s) for each SCM. (please refer to Section V for more information)	
4.	Appropriate permit application processing fee per NCGS 143-215.3D(e)(2) payable to NCDEQ. A full list of fee adjustments is available on the DEQ website: https://www.deq.nc.gov/accessdeq/permit-fees-2023-updates (For an Express review, refer to: https://www.deq.nc.gov/accessdeq/express-permitting for information on the Express program and the associated fees. Contact the appropriate Coastal regional office Express Permit Coordinator for additional information and to schedule the required application meeting.)	DMK
	A detailed narrative (one to two pages) describing the stormwater treatment/management for the project. This is required in addition to the brief summary provided in the Project Information, item 1.	DAK
6.	A USGS map identifying the site location. If the receiving stream is reported as class SA or the receiving stream drains to class SA waters within ½ mile of the site boundary, include the ½ mile radius on the map.	DMK
7	Spaled signed and dated calculations (one copy).	1-11-11

8.	Two sets of plans folded to 8.5" x 14" (sealed, signed, & dated), including:	FAC
	a. Development/Project name.	
	b. Engineer and firm.	
	c. Location map with named streets and NCSR numbers.	
	d. Legend.	
	e. North arrow.	
	f. Scale.	
	g. Revision number and dates.	
	h. Identify all surface waters on the plans by delineating the normal pool elevation of impounded structures, the banks of streams and rivers, the MHW or NHW line of tidal	
	waters, and any coastal wetlands landward of the MHW or NHW lines.	
	Delineate the vegetated setback landward from the normal pool elevation of impounded	
	structures, the banks of streams or rivers, and the MHW (or NHW) of tidal waters.	
	i. Dimensioned property/project boundary with bearings & distances.	
	j. Site Layout with all BUA identified and dimensioned.	
	k. Existing contours, proposed contours, spot elevations, finished floor elevations.	
	1. Details of roads, drainage features, collection systems, and stormwater control measures	
	(including any applicable SCM planting plans).	
	m. Wetlands delineated, or a note on the plans that none exist. (Must be delineated by a	
	qualified person; identify the person who made the determination on the plans. n. Existing drainage (including off-site), drainage easements, pipe sizes, runoff calculations.	
	o. Drainage areas delineated (included in the main set of plans, not as a separate document).	
9.	Copy of any applicable soils report with the associated SHWT <u>elevations</u> (Please identify	DAK
Э.	elevations in addition to depths) as well as a map of the boring locations with the existing	
	elevations and boring logs. Include an 8.5"x11" copy of the NRCS County Soils map with the	
	project area clearly delineated. For projects with infiltration SCMs, the report should also	
	include the soil type, expected infiltration rate, and the method of determining the infiltration rate.	
	(Infiltration Devices submitted to WiRO: Schedule a site visit for DEMLR to verify the SHWT	
	Prior to submittal, (910) 796-7378.)	
	A copy of the most current property deed. Deed book: <u>1554</u> Page No: <u>578</u>	DMK
11,	For corporations and limited liability corporations (LLC): Provide documentation from the NC	DAK
	Secretary of State or other official documentation, which supports the titles and positions held	
	by the persons listed in Contact Information, item 1a, 2a, and/or 3a per 15A NCAC 2H.1040(1).	
	The corporation or LLC must be listed as an active corporation in good standing with the NC Secretary of State, otherwise the application will be returned.	
	http://www.secretary.state.nc.us/Corporations/CSearch.aspx	1
12	If the applicant is not the property owner, a copy of a lease agreement, affidavit, or other	MX
12.	document showing that the applicant has obtained legal rights to submit a stormwater permit	
	application within the proposed project area;	7.
13	If applicable, a copy of any recorded drainage, maintenance, or operation and maintenance	W/A
	easements demonstrating ownership interest sufficient to operate the SW system.	
	Deed book: Page No: Relevant section:	
14.	If a modification to an existing permit:	1.
	a. The applicant / permit holder will remain the same and permit has not and will	NIN
	not expire within the next 180 days.	C
	b. Signed, sealed & dated Designer Certification Forms	
	c. Copies of the following documents recorded with the County Register of Deeds	
	 Deed restrictions and protective covenants limiting the BUA so that it does not exceed the capacity of the SCM(s) or the BUA thresholds. 	
	ii. Drainage easements, when applicable.	
	iii. Operation & Maintenance Agreement	
	iv. Final subdivision plat referencing the Operation & Maintenance Agreement	

VII. DEED RESTRICTIONS AND PROTECTIVE COVENANTS

For all subdivisions, outparcels, and future development, the appropriate property restrictions and protective covenants are required to be recorded prior to the sale of any lot. If lot sizes vary significantly or the proposed BUA allocations vary, a table listing each lot number, lot size, and the allowable built-upon area must be provided as an attachment to the completed and notarized deed restriction form. The appropriate deed restrictions and protective covenants forms can be downloaded from https://www.deg.nc.gov/about/divisions/energy-mineral-and-land-resources/stormwater-program/post-construction-program/post-construction-forms. Download the latest versions for each submittal.

In the instances where the applicant is different than the property owner, it is the responsibility of the property owner to sign the deed restrictions and protective covenants form while the applicant is responsible for ensuring that the deed restrictions are recorded.

By the notarized signature(s) below, the permit holder(s) certify that the recorded property restrictions and protective covenants for this project, if required, shall include all the items required in the permit and listed on the forms available on the website, that the covenants will be binding on all parties and persons claiming under them, that they will run with the land, that the required covenants cannot be changed or deleted without concurrence from the NC DEMLR, and that they will be recorded prior to the sale of any lot.

VIII. CONSULTANT INFORMATION AND AUTHORIZATION

Applicant: Complete this section if you wish to designate authority to another individual and/or firm (such as a consulting engineer and/or firm) so that they may provide information on your behalf for this project (such as addressing requests for additional information).

Consulting Engineer: David M. Klebitz, P.E.	
Consulting Firm: Bissell Professional Group	
Mailing Address: P.O. Box 1068	
City:Kitty Hawk	State: NC Zip: 27949
Phone: (252) 261-3266	Fax: (252) 261-1760
Email: davek@bissellprofessionalgroup.com	

IX. PROPERTY OWNER AUTHORIZATION (if Contact Information, item 2 has been filled out, complete this section)
I, (print or type name of person listed in Contact Information, item 2a) \\ \text{Own the property identified in this permit application, and thus give permission to (print or type name of person listed in Contact Information, item 1a) \\ \text{Contact Information, item 1a} \\ \text{to develop the project as currently proposed. A copy of the lease agreement or pending property sales contract has been provided with the submittal, which indicates the party responsible for the operation and maintenance of the stormwater system.}
As the legal property owner I acknowledge, understand, and agree by my signature below, that if my designated agent (entity listed in Contact Information, item 1) dissolves their company and/or cancels or defaults on their lease agreement, or pending sale, responsibility for compliance with the DEMLR Stormwater permit reverts back to me, the property owner. As the property owner, it is my responsibility to notify DEMLR immediately and submit a completed Name/Ownership Change Form within 30 days; otherwise I will be operating a stormwater treatment facility without a valid permit. I understand that the operation of a stormwater treatment facility without a valid permit is a violation of NC General Statue 143-215.1 and may result in appropriate enforcement action including the assessment of civil penalties of up to \$25,000 per day, pursuant to NCGS 143-215.6.
Signature: Date: 127 25
County of, do hereby certify that, 2025, and acknowledge the
due execution of the application for a stormwater permit. Witness my hand and official seal,
Lig Hales
Christy Hanks NOTARY PUBLIC Dare County, NC My Commission Expires November 05, 2029
SEAL
My commission expires November 05, 2029

X. APPLICANT'S CERTIFICATION

I, (print or type name of person listed in Contact Information, item 1a) Moncertify that the information included on this permit application form is, to the that the project will be constructed in conformance with the approved plans and protective covenants will be recorded, and that the proposed project coapplicable stormwater rules under 15A NCAC 2H .1000 and any other appl	be best of my knowledge, correct and that the required deed restrictions complies with the requirements of the
Signature: The Shellow	Date: 1/37/35
I, Christy Hanks , a Notary Public for the St	
County of Dare , do hereby certify that Monica	Thibaleau
personally appeared before me this 27 day of 300000	\downarrow , 2025 , and acknowledge the
Christy Hanks NOTARY PUBLIC Dare County, NC My Commission Expires November 05, 2029	and official seal,
SEAL	
My commission expires November 05, 2029	A A STATE STATE OF THE PARTY OF

APPLICATION IDENTIFICATION		N.C.	N.C. DEPARTMENT OF TRANSPORTATION				
Driveway Permit No.	Date	of lication 1-24-	25		STREET A	ND DRIVEWAY	ACCESS
County: Curritud		iication			PER	MIT APPLICATI	ON
	ame: Big Box, LLC	Commercial Sit	te Development				
Development 14	arrie. Dig box, LLO		OCATION OF F	ROPERTY:			
Route/Road:	Caratoke Hwy.						
Exact Distance	170	Miles	NSEW	ı			
		☐ Milles ☐ Feet					
From the Interse	ection of Route No.	SR 1106	and Route	No. US Hw	y 158	Toward Jar	visburg
Property Will Be	Used For: 🔲 Resi	dential /Subdivision	n ⊠ Commercial [☐ Educational Fa	cilities 🗀 TND	☐ Emergency Sc	ervices D Other
Property:		⊠is	☐ is not	within Currituc			oning Area.
			AGREEM	ENT			
I agree to construction I agree that it I agree to path application is I agree to conthe public tra I agree to protection I agree to protection I agree to indiffer damage the indifference in it agree to protect in it agree to protect in it agree to protect indifference in its indi	no signs or objects he driveway(s) or a hat driveway(s) or a sa deemed nece of any future improvablic right-of-way was titled to reimburse his permit become or on Street and Drive a \$50 construction denied. Instruct and maintained a deried and Amendments of the District Enginematify and save he hat may arise by refer North Carolina in the District Enginematify and save he hat may arise by refer North Carolina in the District Enginematify and save he hat may arise by refer North Carolina in the North Carolina in the North Carolina in the Sof this permit is suffernit in the N.C. he entire cost of cost of this permit will NOTIFY THE DIS	will be placed street(s) will be street(s) as us ssary. Verments to the will be consider ment or have a se void if constructions and Indemnitate Highway subject to the regression of process on inspection for the highway right and Indemnitate Highway subject to the regression of the policy on Drive onstructing and I be borne by the street of the policy on the polic	on or over the pro- e constructed as a defined in this agreent of the property owners of the proper	dopted by the ublic right-of-washown on the nent include a encessary, to the North Casent expenditury (s) or street (a Highways". It is payable to North a safe mannary as a safe mannary and the north encent of Traill assume no in carrying our mount specified of the NC Deprot be constructed approved privater, the application as to the safe mannary or the north encent of the NC Deprot be constructed approved privater, the application as to the safe mannary or the north encent of the NC Deprot be constructed privater, the application and the north encent of the NC Deprot be constructed privater, the application and the north encent of the north encent enc	e North Carol vay other tha attached pla iny approach he portion of arolina Depa ures for drive (s) is not con CDOT. This er so as not is, flaggers a Traffic Contro above rules ransportation responsibilit at its construct d by the Divi- artment of Traffic d as a cont ate street or int, and their	ina Department in those approvens. In tapers, storage of driveway(s) or artment of Transeway or street completed within the fee will be reinful to interfere with and other warning of Devices for Sand regulations of From all damages for any damages of the fee will be reinful to interfere with and other warning of Devices for Sand regulations of Highwar ansportation are access point of the fee will be reinful to interfere with and other warning of the fee will be reinful to interfere with any fee and regulations of Highwar ansportation are access point of the fee will be reinful to interfere with a fe	t of yed by NCDOT. e lanes or speed street(s) sportation, and I onstruction. he time specified hoursed if n or endanger ng devices for Streets and s may be ges and claims ages that may be ays for any s provided by int. ss connection essors, and
2004-07 NO	OTE: Submit Four Co	opies of Application	on to Local District E 61-03419	Engineer, N.C. D	epartment of ⁻	Transportation	TEB 65-04rev.

SIGNATURES OF APPLICANT					
COMPANÝ SIGNATURE ADDRESS	PROPERTY OWNER (APPLICANT) Big Box, LLC c/o Monica Thibodeau, Reg. Agent 1197 Duck Road Duck, NC 27949 Phone No. 252-261-3934	NAME SIGNATURE ADDRESS	WITNESS Chaisty Hanks Cof Hales 4120 Poor Ridge 12d City Hank No 27949		
COMPANY SIGNATURE ADDRESS	AUTHORIZED AGENT Bissell Professional Group 3512 N. Croatan Highway Kitty Hawk, NC 27949 Phone No. 252-261-3266 APPRO	NAME SIGNATURE ADDRESS	Marcie Despass Marcie Despass Marcie Respons Po Box 1068 Kithy Hack, NC 25645		
APPLICATION	RECEIVED BY DISTRICT ENGINEER				
	SIGNATURE		DATE		
APPLICATION A	APPROVED BY LOCAL GOVERNMENTAL AUTHORITY (when	required)			
	SIGNATURE	TITLE	DATE		
APPLICATION A	APPROVED BY NCDOT SIGNATURE	TITLE	DATE		
INSPECTION B	YNCDOT				
	SIGNATURE	TITLE	DATE		
COMMENTS:					

.

ROUTE	US HWY 158	_ PROJECT	Big Box, LLC	COUNTY	OF Currituck	NORTH CAROLINA
DEP	ARTMENT OF TRANS	PORTATION		THR	EE PARTY RIGHT	OF WAY
	-AND-			ENCR	DACHMENT AGRE	EMENT ON
Bi	g Box, LLC c/o Monica	Thibodeau		PRIMAR	RY AND SECONDA	ARY SYSTEM
1	197 Duck Road, Duck	NC 27949				
	-AND-					
C	ounty of Currituck, Nor	th Carolina				
153 (Courthouse Rd. Curritu	ck, NC 27929				
THIS AG	THIS AGREEMENT, made and entered into this the day of, 20, by and between the Department					
of Transp	ortation, party of the fir	st part; and Big	Box, LLC c/o Monic	a Thibodeau		
				econd part; and	County of Curri	tuck, North
Carolina					party of th	e third part,
WITNESSETH						
THA	T WHEREAS, the part	y of the second	part desires to encro	ach on the right of	way of the public r	oad designated as
Route(s)	US HWY 158 (Cara	toke Hwy)		located Approx.	190 feet north from	n the intersection
with SR 1	106 (Halls Harbor Rd.)	towards Jarvish	ourg			
with the co	onstruction and/or erec	tion of: Fire	Hydrant and water se	rvice installations	to serve proposed	commercial
develo	pment					

WHEREAS, it is to the material advantage of the party of the second part to effect this encroachment, and the party of the first part in the exercise of authority conferred upon it by statute, is willing to permit the encroachment within the limits of the right of way as indicated, subject to the conditions of this agreement;

NOW, THEREFORE, IT IS AGREED that the party of the first part hereby grants to the party of the second part the right and privilege to make this encroachment as shown on attached plan sheet(s), specifications and special provisions which are made a part hereof upon the following conditions, to wit:

That the installation, operation, and maintenance of the above described facility will be accomplished in accordance with the party of the first part's latest POLICIES AND PROCEDURES FOR ACCOMMODATING UTILITIES ON HIGHWAY RIGHTS-OF-WAY, and such revisions and amendments thereto as may be in effect at the date of this agreement. Information as to these policies and procedures may be obtained from the Division Engineer or State Utility Agent of the party of the first part.

That the said party of the second part binds and obligates himself to install and maintain the encroaching facility in such safe and proper condition that it will not interfere with or endanger travel upon said highway, nor obstruct nor interfere with the proper maintenance thereof, to reimburse the party of the first part for the cost incurred for any repairs or maintenance to its roadways and structures necessary due to installation and existence of the facilities of the party of the second part, and if at any time the party of the first part shall require the removal of or changes in the location of the said facilities, that the said party of the second part binds himself, his successors and assigns, to promptly remove or alter the said facilities, in order to conform to the said requirement, without any cost to the party of the first part.

That the party of the second part agrees to provide during construction and any subsequent maintenance proper signs, signal lights, flagmen and other warning devices for the protection of traffic in conformance with the latest <u>Manual on Uniform Traffic Control Devices</u> for Streets and <u>Highways</u> and Amendments or Supplements thereto. Information as to the above rules and regulations may be obtained from the Division Engineer of the party of the first.

That the party of the second part hereby agrees to indemnify and save harmless the party of the first part from all damages and claims for damage that may arise by reason of the installation and maintenance of this encroachment.

That the party of the second part agrees to restore all areas disturbed during installation and maintenance to the satisfaction of the Division Engineer of the party of the first part. The party of the second part agrees to exercise every reasonable precaution during construction and maintenance to prevent eroding of soil; silting or pollution of rivers, streams, lakes, reservoirs, other water impoundments, ground surfaces or other property; or pollution of the air. There shall be compliance with applicable rules and regulations of the North Carolina Division of Environmental Management, North Carolina Sedimentation Control Commission, and with

ordinances and regulations of various counties, municipalities and other official agencies relating to pollution prevention and control. When any installation or maintenance operation disturbs the ground surface and existing ground cover, the party of the second part agrees to remove and replace the sod or otherwise reestablish the grass cover to meet the satisfaction of the Division Engineer of the party of the first part.

That the party of the second part agrees to assume the actual cost of any inspection of the work considered to be necessary by the Division Engineer of the party of the first part.

That the party of the second part agrees to have available at the construction site, at all times during construction, a copy of this agreement showing evidence of approval by the party of the first part. The party of the first part reserves the right to stop all work unless evidence of approval can be shown.

Provided the work contained in this agreement is being performed on a completed highway open to traffic; the party of the second part agrees to give written notice to the Division Engineer of the party of the first part when all work contained herein has been completed. Unless specifically requested by the party of the first part, written notice of completion of work on highway projects under construction will not be required.

That in the case of noncompliance with the terms of this agreement by the party of the second part, the party of the first part reserves the right to stop all work until the facility has been brought into compliance or removed from the right of way at no cost to the party of the first part.

That it is agreed by both parties that this agreement shall become void if actual construction of the work contemplated herein is not begun within one (1) year from the date of authorization by the party of the first part unless written waiver is secured by the party of the second part from the party of the first part.

During the performance of this contract, the second party, for itself, its assignees and successors in interest (hereinafter referred to as the "contractor"), agrees as follows:

- a. <u>Compliance with Regulations</u>: The contractor shall comply with the Regulations relative to nondiscrimination in Federally-assisted programs of the U. S. Department of Transportation, Title 49, Code of Federal Regulations, Part 21, as they may be amended from time to time, (hereinafter referred to as the Regulations), which are herein incorporated by reference and made a part of this contract.
- b. <u>Nondiscrimination</u>: The contractor, with regard to the work performed by it during the contract, shall not discriminate on the grounds of race, color, or national origin in the selection and retention of subcontractors, including procurements of materials and leases of equipment. The contractor shall not participate either directly or indirectly in the discrimination prohibited by Section 21.5 of the Regulations, including employment practices when the contract covers a program set forth in Appendix B of the Regulations.
- c. <u>Solicitations for Subcontracts, including Procurements of Materials and Equipment</u>: In all solicitations either by competitive bidding or negotiation made by the contractor for work to be performed under a subcontract, including procurements of materials or leases of equipment, each potential subcontractor or supplier shall be notified by the contractor of the contractor's obligations under this contract and the Regulations relative to nondiscrimination on the grounds of race, color, or national origin.
- d. <u>Information and Reports</u>: The contractor shall provide all information and reports required by the Regulations, or directives issued pursuant thereto, and shall permit access to its books, records, accounts, other sources of information, and its facilities as may be determined by the Department of Transportation or the Federal Highway Administration to be pertinent to ascertain compliance with such Regulations or directives. Where any information required of a contractor is in the exclusive possession of another who fails or refuses to furnish this information, the contractor shall so certify to the Department of Transportation, or the Federal Highway Administration as appropriate, and shall set forth what efforts it has made to obtain the information.
- e. <u>Sanctions for Noncompliance</u>: In the event of the contractor's noncompliance with the nondiscrimination provisions of this contract, the Department of Transportation shall impose such contract sanctions as it or the Federal Highway Administration may determine to be appropriate, including, but not limited to,
 - (1) withholding of payments to the contractor under the contract until the contractor complies, and/or
 - (2) cancellation, termination or suspension of the contract, in whole or in part.
- f. Incorporation of Provisions: The contractor shall include the provisions of paragraphs "a" through "f" in every subcontract, including procurements of materials and leases of equipment, unless exempt by the Regulations, or directives issued pursuant thereto. The contractor shall take such action with respect to any subcontract or procurement as the Department of Transportation or the Federal Highway Administration may direct as a means of enforcing such provisions including sanctions for noncompliance: Provided, however, that, in the event a contractor becomes involved in, or is threatened with, litigation with a subcontractor or supplier as a result of such direction, the contractor may request the Department of Transportation to enter into such litigation to protect the interests of the State, and, in addition, the contractor may request the United States to enter into such litigation to protect the interests of the United States.

That when title to the subject that constitutes the aforesaid encroachment passes from the party of the second part and vests in the party of the third part, the party of the third part agrees to assume all responsibilities and rights and to perform all obligations as agreed to herein by the party of the second part.

R/W (166): Party of the Second Part certifies that this agreement is true and accurate copy of the form R/W (166) incorporating all revisions to date.

IN WITNESS WHEREOF, each of the parties to this agreement has caused the same to be executed the day and year first above written.

	DEPARTMENT OF TRANSPORTATION
WITNESS:	BY: DIVISION ENGINEER
Chaisey Hanks Out Haks 4120 Poor Ridge Rd.	Big Box, LLC c/o Monica Thibodeau
KITY HOUR NC 27949 WITNESS:	Second Party
	County of Currituck, North Carolina
	Third Party